

# PALLET JACK STANDARD



## Frame

- Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

## Forks

- Reinforced for added strength with tapered ends for easy pallet entry.

## Paint

- The CJ55 series boasts a quality Powder Coat finish.

## Hydraulic Pump

- Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload by-pass valve.

## Handle

- Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

## Control Handle

- The control handle has three positions (raise/neutral/lower) fingertip control. Ergonomically designed and free of pinch points.

## Pump Stroke

- Features a full 90 degree top to bottom stroke requires only 10 strokes to raise the forks to the maximum lift.

## Load Rollers

- Features 2.9" polyurethane rollers with sealed bearings.

## Steering

- Featuring 200 degree pivot action for greater maneuverability with 7" polyurethane wheels, sealed bearings and "Ball-Thrust" steering.

## Hangers

- The one piece hangers are constructed of Iron Cast for greater strength and longevity.

## Helper Rollers

- Features 4 helper rollers for easy exit and entry of pallets.

## Pivot Points

- The CJ55 features grease fittings and bushings at all pivot points for easy maintenance.



## CJ55

Load Capacity	5500 lbs.
Fork Length	48"
Overall Fork Widths	20.5"/27"
Lowered Fork Height	2.9"
Raised Fork Height	7.8"
Fork Width	6.5"
Weight	170 lbs.
Steer Wheels	7"
Load Rollers	2.9" x 3.6"
Wheels/Rollers	Polyurethane