# PACCAR MX-11



## PACCAR MX-11

### Powered By Quality



- **Uptime:** MX-11 engines are built for durability with a B10 rating of over one million miles. Every MX-11 engine also comes standard with remote diagnostics to deliver focused uptime support.
- Excellent Fuel Economy: With ratings to 430 hp and 1,650 lb-ft of torque, downsizing for fuel economy no longer means compromising performance.
- Low Cost of Service: With a 75,000 mile oil change interval, our MX engines will save your business money with a low cost of routine maintenance over the life of the engine.
- Weight Savings Help Increase Revenue: Less engine weight means hauling more payload with every trip. The PACCAR MX-11 engine is lighter than a 13L engine by 400 lbs.
- **Superior Performance & Quiet Operation:** An MX engine's broad torque curves require less shifting, and the quiet operation improves the driving experience.

#### RATINGS

PEAK HORSEPOWER (HP)	Peak Torque (lb-ft @ rpm)		
430	1,650 @ 900		
430 MT	1,450/1,650 @ 900		
415	1,550 @ 900		
400	1,450 @ 900		
375	1,350 @ 900		
355	1,250 @ 900		
335	1,150@ 900		

<sup>&</sup>lt;sup>1</sup>Multi Torque Rating

#### **SPECIFICATIONS**


Configuration	INLINE 6-CYLINDER	
BORE X STROKE	123 х 152 (мм)	
DISPLACEMENT	10.8 liters	
Dry Weight	2,200 lbs.	
OIL SYSTEM CAPACITY	39 U.S. quarts	
Horsepower	335-430 нр	
PEAK TORQUE	1,150-1,650 lbft.	
GOVERNED SPEED	2,200 грм	
CLUTCH ENGAGEMENT TORQUE <sup>2</sup>	737 гвгт. @ 800 грм	
B10 Design Life	1,000,000 miles/ 1,600,000 km	
Base Warranty <sup>3</sup>	2 Years/250,000 miles/400,000 km	


<sup>&</sup>lt;sup>2</sup>Determined By Engine Horsepower And Idle Setting , <sup>3</sup>Extended Protection Plans Available

#### MAINTENANCE INTERVALS

Maintenance Item		MILES	KILOMETERS
OIL AND FILTER	- Severe\Vocational Duty	30,000	48,000
	- Normal \Line Haul > 20% Idle Time	50,000	80,000
	- Normal\Line Haul < 20% Idle Time	75,000	120,000
FUEL FILTER	- Severe\Vocational Duty <sup>4</sup>	30,000	48,000
	- Normal \Line Haul > 20% Idle Time $^4$	50,000	80,000
	- Normal\Line Haul < 20% Idle $Time^4$	75,000	120,000
COOLANT FILTER - SEVERE\VOCATIONAL DUTY		300,000	480,000
	- Normal\Line Haul	300,000	480,000
DEF FILTER		300,000	480,000

<sup>&</sup>lt;sup>4</sup>Engine Mounted Fuel Filter







- Single Canister DPF and SCR Aftertreatment Design
- Simplified Packaging
- Light Weight

PACCAR Inc P.O. Box 1518 Bellevue, WA 98009

